



6.5 & 8 FT. V-BOX

SPREADERS

SALT & SAND SPREADERS

- Available in stainless steel (6.5' & 8') or carbon steel (8')
- New swing-away spinner chute for easier unloading and improved trailer hitch access
- In-cab electric control of starter, throttle, and clutch functions
- Briggs & Stratton Intek AVS OHV engine
- Optional easy-access hinged hopper grids



Snow removal contractors looking for extra profits will find them in ice control.

Spread salt, sand, or chips quickly and easily with a Hiniker high-capacity 1.5 or 1.8 yard V-box spreader.

◀ A convenient swing-away spinner chute provides faster cleanout and easy trailer hitch access.

HINIKER SALT & SAND SPREADERS



Optional 2 Piece Hinged Screens



Easily adjustable deflectors allow customized spread patterns up to 25 ft. wide

Hopper: Formed and welded with continuous electric seam welding on the inside of hopper. The top edge is formed for rigidity. Side slope of 45 degrees allows smooth material flow. An adjustable self-locking feed gate with lever is standard.

Conveyor: Heavy-duty, self-cleaning, heat-treated pintle chain with 24,000 lb. tensile strength. Two screw-type adjusters are provided to take up chain slack.

Spinner: 14-gauge spinner chute assembly with three external adjustable material deflectors provided to control spread pattern. Spinner disc is 12-inch diameter with three welded fins. Spinner shaft of 3/4" diameter steel is mounted with sealed, self-aligning bearing.

Gear Case: The conveyor gear case has a cast-iron housing. A precision-machined, hardened and ground steel worm gear drives a heavy-duty bronze spur gear. Both gears and bearing run in oil and are sealed from contaminants.

Conveyor Drive: Briggs & Stratton Intek OHV air-cooled, single cylinder, four-cycle engine is mounted on the rear of the spreader. The engine is equipped with an air cleaner, 12V battery, 12V electric starter, and electric throttle control. An in-cab control panel has engine start, shut-off, throttle, and clutch control functions. A hinged engine hood fully encloses the engine. An electric clutch engages and disengages the drive sprocket. Power is transferred to the gear case through roller chain and sprockets.

Optional Equipment:

- 2 Piece Hinged Hopper Screens
- Adjustable Inverted "V"
- Ratchet Strap Tie Downs
- 12-inch Side Extensions
- High-mount Brake Light

HINIKER Specifications:

	LEVEL CAPACITY	LENGTH	TOP WIDTH
MODEL 815/825	1.80 Cubic Yards	115" Overall/96" Hopper	50.5"
MODEL 625	1.50 Cubic Yards	97" Overall/78" Hopper	50.5"

WE RESERVE THE RIGHT TO AMEND THESE SPECIFICATIONS AT ANY TIME WITHOUT NOTICE. THE ONLY WARRANTY APPLICABLE IS OUR STANDARD WRITTEN WARRANTY. WE MAKE NO OTHER WARRANTY, EXPRESSED OR IMPLIED.



PUT SNOW IN ITS PLACE

HINIKER COMPANY
 58766 240 St • P.O. Box 3407
 Mankato, MN 56002-3407
 Phone (507) 625-6621
 Fax (507) 625-5883
www.hiniker.com