

# HINIKER SNOWPLOWS



## Get Professional Performance With Hiniker Straight Blade Plows



Take a professional approach to snow removal! Hiniker Snowplows use box section frames and heavily reinforced moldboards for strength and durability. 30 inch tall high-curve moldboards move heavy

snowfalls quickly. Our hydraulic scissors lift reduces transport bounce and bang. Convenient compact joystick controls can be mounted anywhere or held in the palm of your hand. And the Hiniker Quick-Hitch mounting system is one system that truly lives up to its name.

***Count on Hiniker's proven performance—the professionals choice!***



## Quick Hitch MOUNTING SYSTEM

The Hiniker Quick Hitch is the fastest plow mounting system available. The self-aligning drive-in mount lets you connect your Hiniker plow in seconds. This eliminates manually lifting, pushing, and pulling the plow into place.



- 1 Drive truck forks into plow receiver
- 2 Pull lever to lock plow to truck & raise stand
- 3 Plug in connections & you're ready to roll!



Reverse the process to disconnect the entire plow assembly just as quickly, leaving it ready for the next snow. Because Hiniker makes it so easy to disconnect your plow, you'll save weight and wear on your truck when the plow is not needed.



Convenient, compact fingertip control mounts anywhere or can be hand held.



Optional Flexstand allows controls to be positioned right where you want them.



Hiniker's optional Box Ends decrease spillage and increase removal capacity. Attachment is fast and easy.



Optional Bolt-on Curb Guard.

• Optional molded poly or spring-loaded rubber (shown) snow deflectors.

• 30" tall, high curve blade rolls snow off quickly.

• Entire moldboard trips with soft-return compression springs.

• Robotic blade & frame welds assure uniform quality.

• Externally mounted pump simplifies installation, comes off the truck with the plow.

• Hydraulic scissors lift cuts transport bounce, eliminates chains.

• Heavy-duty box section plow frame resists twisting & bending.

• Halogen head lamps are operated by truck light switch.

## HINIKER CONVENTIONAL PLOW

### *Specifications:*

BLADE WIDTH	7 1/2'	8'	8 1/2'
BLADE HEIGHT	30"	30"	30"
GAUGE OF STEEL	12GA	12GA	12GA
VERTICAL RIBS	6	6	8
COMPRESSION TRIP SPRINGS	2	2	4
PLOW WIDTH @ 31° ANGLE	77"	82"	87"
CUTTING EDGE (HIGH CARBON 1084 STEEL)	3/8" x 6"	3/8" x 6"	3/8" x 6"
POWER ANGLING RAMS	1 1/2" x 10"	1 1/2" x 10"	1 1/2" x 10"
WEIGHT (NET OF TRUCK MOUNTED HARDWARE)	603 lbs.	614 lbs.	649 lbs.

WE RESERVE THE RIGHT TO AMEND THESE SPECIFICATIONS AT ANY TIME WITHOUT NOTICE. THE ONLY WARRANTY APPLICABLE IS OUR STANDARD WRITTEN WARRANTY. WE MAKE NO OTHER WARRANTY, EXPRESSED OR IMPLIED.



**HINIKER COMPANY**  
 58766 240 St. • P.O. Box 3407  
 Mankato, MN 56002-3407  
 Phone (507) 625-6621  
 Fax (507) 625-5883  
[www.hiniker.com](http://www.hiniker.com)