

HIMIKER

V-PLOW

HIGH-PERFORMANCE TRIP-EDGE PLOW

- Exclusive high pivot point trip-edge
- Super-bright quad halogen lights
- Double acting hydraulic power





Take The Professional Approach to Snow Removal Put more muscle on the job with the leaner, stronger 9000 series

Put more muscle on the job with the leaner, stronger 9000 series V-Plows from Hiniker. Add power and profit to your plowing season with the Hiniker V-Plow.








The high-tensile steel superstructure of the moldboard provides exceptional resistance to bending and bowing, for extra heavy-duty applications. 12 laser-cut steel ribs add exceptional strength.

Hydraulic scissors lift cuts transport bounce, eliminates lift chains.



The compact joystick control puts full control of all plow functions in the palm of your hand.

New super-bright quad halogen headlights have up to twice the power of typical sealed beam lamps. Get maximum visibility for added safety, and better, faster plowing operations.





Long-lasting — cast ductile-iron skid shoes.

30-inch tall high curve, high-density polyethylene moldboards are dent-free and corrosion-free. Snow flows easily for more efficient plowing. Optional rubber or polyethylene snow deflectors.

Double-acting cylinders

control of moldboard

provide positive hydraulic

position, whether plowing forward or backdragging.



SPEED, EASE, & SIMPLICITY



The Hiniker Quick Hitch is the fastest plow mounting system available! The self-aligning drive-in mount lets you connect your Hiniker plow in seconds. This eliminates manually lifting, pushing, and pulling the plow into place.

- Drive truck forks into plow receiver
- Pull lever to lock plow to truck
 & raise stand
- Plug in connections & you're ready to roll!

Reverse the process to disconnect the entire plow assembly just as quickly, leaving it ready for the next snowfall. Because Hiniker makes it so easy to disconnect your plow, you'll save weight and wear on your truck when the plow is not needed.

6" high-carbon — steel replaceable cutting edge.

independently of one another, reducing stress and twisting forces on the plow.

HINIKER **Specifications:**

Pinch-free pivot point is 9 inches above the – surface providing protection from higher obstacles such as curbs and parking barriers.

		Model 9850	Model 9950
		8 ½ ft	9½ft
CUTTING WIDTH	V-POSITION:	93.5"	104"
	SCOOP:	83.5"	94"
	STRAIGHT:	102"	114"
	ANGLE:	88.5"	99"
WEIGHT (net of truck mounted hardware):		798 lb.	826 lb.
MOLDBOARD HEIGHT:		30 inches	
MOLDBOARD SURFACE:		1/4" HMW Poly	
TRIP SPRINGS:		4	
STANDARD CUTTING EDGE:		3/8" x 6" high-carbon steel	

High clearance trip-edges operate -

WE RESERVE THE RIGHT TO AMEND THESE SPECIFICATIONS AT ANY TIME WITHOUT NOTICE. THE ONLY WARRANTY APPLICABLE IS OUR STANDARD WRITTEN WARRANTY. WE MAKE NO OTHER WARRANTY, EXPRESSED OR IMPLIED.



HINIKER COMPANY

58766 240 St • P.O. Box 3407 Mankato, MN 56002-3407 Phone (507) 625-6621 Fax (507) 625-5883 www.hiniker.com